

## Digital Indicator MarCator1086 WR

### Features

#### Function:

ON/OFF, RESET (set display to zero), mm/inch, Reversal of counting direction, PRESET (for entering a numerical value), TOL (enter tolerance limit values), <0> (tolerance GO / NO GO display mode), ABS (display can be set to zero without losing reference to preset), DATA (Data transmission via connection cable), Factor (adjustable), LOCK (individual button lock)

#### Product features:

High contrast LCD

Operating and display unit (bezel) can be rotated through 280°

Protection cap on the end of measuring spindle

Mounting shank and measuring spindle are both made of hardened stainless steel

Immediate measurements due to the Reference System

#### Energy supply:

Battery life approx. 3 years

#### Scope of delivery:

- Instruction manual
- Battery




Order-No.: 4337641

### Technical Data

Measuring span	25 mm
Measuring range in inch	1 in
Resolution	0,0005 mm, 0,001 mm, 0,002 mm, 0,005 mm, 0,01 mm
Resolution inches	.00002", .00005", .0001", .0002", .0005"
Error limit	0,004 mm
Error limit over 25 graduations	0,002 mm
Repeatability mm	0,001 mm
Measuring force	1 - 2.25
Height of digits	11 mm

### Dimensions

Mounting shaft	8 mm
a	193,2 mm
b	24,8 mm
c	50 mm



### Accessories

Bezeichnung	Typ	Artikel-Nr.
Data connection cable USB	16 EXu	4102357
Digimatic data cable	16 EWd	4102915
Data connection cable RS232C	16 EXr	4102410
Lug back	1086 b	4337421
Cable Release	1085 a	4336311
Pneumatic Lifter	1082 p	4336237
Rubber bellows		4337474-E
Adapter bush	940	4310103