



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: SAW Filter 867.5MHz SMD 3.0×3.0mm

TST Parts No.:TA0547A

Customer Parts No.:_____

Company:_____

Division:_____

Approved by :_____

Date:_____

Checked by:_____ Bob Chau

Approval by:_____ Francis Chen

Date:_____ 2006/03/17



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 867.5 MHz

MODEL NO.: TA0547A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dB_m
2. DC voltage: 3 V
3. Operating Temperature: -30°C to +85°C
4. Storage Temperature: -40°C to +85°C



RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:

Item		Specification			
		Unit	Min.	Typ.	Max.
Center Frequency	F _c	MHz	-	867.5	-
Insertion Loss	860~875 MHz	dB	-	1.8	3.5
Ripple	860~875 MHz	dB	-	0.4	1.5
VSWR	860~875 MHz		-	1.25	2.0
Attenuation (Reference from 0dB)					
100 ~ 815	MHz	dB	40	47	-
815 ~ 830	MHz	dB	38	46	-
898 ~ 901	MHz	dB	15	21	-
915 ~ 925	MHz	dB	30	40	-
925 ~2330	MHz	dB	28	33	-
2330 ~3000	MHz	dB	20	25	-
Source impedance	Z _s	Ω	-	50	-
Load impedance	Z _L	Ω	-	50	-


Note1. No matching network required for operation at 50 Ω

C. FREQUENCY CHARACTERISTICS:




Reflection Functions:


S11




S22




D. MEASUREMENT CIRCUIT:



E. OUTLINE DRAWING:




F. PCB FOOTPRINT:




G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION



H.RECOMMENDED REFLOW PROFILE:

