



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date: March, 6, 2006

Product Name: SAW Filter 912 MHz SMD 3.0X3.0 mm

TST Parts No.: TA0556A

Customer Parts No.: _____

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Bob Chau

Approval by: _____ Francis Chen

Date: _____ 3, 6, 2006



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 912MHz

MODEL NO.:TA0556A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -20°C to +70°C
4. Storage Temperature: -30°C to +85°C


RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Type.	Max.	Note
Center Frequency Fc	MHz	-	912	-	-
Insertion Loss (904 ~ 920 MHz) IL	dB	-	1.6	3.3	-
Amplitude Ripple (904 ~ 920 MHz)	dB	-	0.6	2	-
VSWR (904 ~ 920 MHz)		-	1.65	2.4	-
Relative Attenuation (relative to 0 dB)					
D.C. ~ 850 MHz	dB	22	35	-	-
930 ~ 940 MHz	dB	7	32	-	-
940 ~ 1500 MHz	dB	23	37.6	-	-

C. MEASUREMENT CIRCUIT:


HP Network analyzer





D.OUTLINE DRAWING:



E. PCB Footprint:





F. Frequency Characteristics :





Reflections Functions :

S11 VSWR




S22 VSWR



G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION

