



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 911.92 MHz SMD 3.0x3.0 mm (BW=11 MHz)

TST Part No.: TA1894A

Customer Part No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ David Chang 

Approved by: _____ Bob Chau 

Date: _____ 2015/04/28

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 911.92 MHz

MODEL NO.: TA1894A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dB_m
2. DC voltage: 5 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C

RoHS Compliant
Lead free
Lead-free soldering


Electrostatic Sensitive Device (ESD)

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Typ.	Max.
Center frequency F_c	MHz	-	911.92	-
Insertion Loss (906.42~917.42 MHz) IL	dB	-	2.8	4.5
Amplitude Ripple (906.42~917.42 MHz)	dB	-	0.8	2.8
VSWR (906.42~917.42 MHz)	-	-	1.3	2.5
Attenuation (Reference level from 0 dB)				
10 ~ 875 MHz	dB	45	51	-
894 MHz	dB	14	52	-
1005 ~ 1500 MHz	dB	45	56	-
1500 ~ 2000 MHz	dB	40	45	-
Temperature coefficient of frequency	ppm/k	-	-36	-

C. MEASUREMENT CIRCUIT:

HP Network analyzer



D. OUTLINE DRAWING:



B: Input

E: Output

A, C, D, F: Ground

Unit: mm


△ : Year Code (2011->1, 2012->2, ..., 2019->9, 2020->0)

□ : Date Code



Date Code Table:

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

E. PCB Footprint:




F. Frequency Characteristics:




Reflection Functions:

S11



S22



1. REEL DIMENSION

Technical drawing of a circular component. The main view shows a large circle with a central hole. A dashed circle indicates the hole's diameter. A leader line points from the text "See DETAIL 'A'" to the central hole. To the right, a vertical dimension line indicates a distance of "12 TYP." from the top edge to the center of the hole. Below the main view, a detailed view of the hole is shown, labeled "A". It features a central hole with a diameter of $\phi 100 \text{ REF.}$ and an outer diameter of $\phi 330 \text{ REF.}$. The hole is surrounded by a flange with a thickness of 20 ± 0.5 . The flange has a diameter of $\phi 130 \pm 0.5$ and a diameter of $\phi 20.2 \pm 0.5$ for the central hole. The flange is divided into 12 segments, with "12 TYP." indicating the typical distance between segments.

[illegible]

H. RECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 245~260°C peak (min. 10sec).
4. Time: 2 times.

