

DUAL BAND COMBINER

PART NO. : WV-DBC-0819-3N-01

◆ APPLICATION

- > Integrates Wireless Bands(824MHz~894MHz, 1850MHz~1990MHz)
- > Designs for Co-siting systems
- > Indoor/Outdoor Application

◆ FEATURE

- > High Reliability
- > **RoHS Compliant**

◆ ELECTRICAL SPECIFICATION

ITEM	SPECIFICATION	
	Band 1	Band 2
Frequency Range	824MHz ~ 894MHz	1850MHz ~ 1990MHz
Bandwidth	70MHz	140MHz
Insertion Loss	0.15dB Max. @ Band 1(824MHz ~ 894MHz) 0.15dB Max. @ Band 2(1850MHz ~ 1990MHz)	
VSWR	1.12:1 Max	
PIMD	150dBc Min @ 2x43dBm Input	
Isolation	50dB Min	
DC Pass	Band 1 : DC Pass Band 2 : DC Pass	
Maximum Input Power	250W (CW) per input	
In/Out Impedance	50 Ohms Nominal	

◆ ENVIRONMENTAL SPECIFICATIONS

ITEM	SPECIFICATION
Operating Temperature	-35°C to +65°C
Environmental class	IP67

DUAL BAND COMBINER

MECHANICAL SPECIFICATIONS

ITEM	SPECIFICATION
Dimension	165.0 x 129.0 x 87.0 Max (unit:mm)
Mounting Points	Wall or Pole
RF Connector	N Female Connector
Connector Position	See Outline Drawing
Weight	Around 3.0Kg
Finish	Gray color epoxy coating

OUTLINE DRWAING

