

DUAL BAND COMBINER

PART NO. : WV-DBC-0920-3D

◆ APPLICATION

- > Integrates Wireless Bands(890MHz~960MHz, 1710MHz~2170MHz)
- > Designs for Co-siting systems
- > Indoor/Outdoor Application

◆ FEATURE

- > High Reliability
- > **RoHS Compliant**

◆ ELECTRICAL SPECIFICATION

ITEM	SPECIFICATION	
	Band 1	Band 2
Frequency Range	806MHz ~ 960MHz	1710MHz ~ 2170MHz
Bandwidth	155MHz	460MHz
Insertion Loss	0.15dB Typ. @ Band 1(806MHz ~ 960MHz) 0.25dB Typ. @ Band 2(1710MHz ~ 2170MHz)	
VSWR	1.2:1 Max	
PIMD	150dBc Min @ 2x43dBm Input	
Isolation	50dB Min	
DC Pass	Band 1 : DC Pass Band 2 : DC Pass	
Maximum Input Power	250W (CW)	
In/Out Impedance	50 Ohms Nominal	

◆ ENVIRONMENTAL SPECIFICATIONS

ITEM	SPECIFICATION
Operating Temperature	-40°C to +60°C
Environmental class	IP65

◆ Accessory

Grounding cable	Included, 1mt of tin plated cooper AWG7 with terminals in both ends
-----------------	---

DUAL BAND COMBINER

◆ MECHANICAL SPECIFICATIONS

ITEM	SPECIFICATION
Dimension	180.0 x 145.6 x 60.0 Max (unit:mm)
Mounting Points	Wall or Pole
RF Connector	7/16 DIN Female Connector
Connector Position	See Outline Drawing
Weight	1.6Kg
Finish	Black color epoxy coating

◆ OUTLINE DRWAING

