

DUAL BAND COMBINER

PART NO. : WV-DBC-1821-3D

◆ APPLICATION

- > Integrates Wireless Bands(1710MHz~1880MHz, 1920MHz~2170MHz)
- > Designs for Co-siting systems
- > Indoor/Outdoor Application

◆ FEATURE

- > High Reliability
- > **RoHS Compliant**

◆ ELECTRICAL SPECIFICATION

ITEM	SPECIFICATION	
	Band 1	Band 2
Frequency Range	1710MHz ~ 1880MHz	1920MHz ~ 2170MHz
Bandwidth	170MHz	250MHz
Insertion Loss	0.4dB Max. @ Band 1(1710MHz ~ 1880MHz) 0.4dB Max. @ Band 2(1920MHz ~ 2170MHz)	
VSWR	1.22:1 Max	
PIMD	150dBc Min @ 2x43dBm Input	
Isolation	50dB Min	
DC Pass	Band 1 : DC Pass Band 2 : DC Pass	
Maximum Input Power	150W (CW)	
In/Out Impedance	50 Ohms Nominal	

◆ ENVIRONMENTAL SPECIFICATIONS

ITEM	SPECIFICATION
Operating Temperature	-20°C to +60°C
Environmental class	IP65

◆ ACCESSORY

ITEM	SPECIFICATION
Grounding cable	Included, 1mt of tin plated cooper AWG7 with terminals in both ends

DUAL BAND COMBINER

MECHANICAL SPECIFICATIONS

ITEM	SPECIFICATION
Dimension	186.0 x 160.7 x 70.0 Max (unit:mm)
Mounting Points	Wall or Pole
RF Connector	7/16 DIN Female Connector
Connector Position	See Outline Drawing
Weight	4.0Kg
Finish	Black color epoxy coating

OUTLINE DRWAING

